Product data sheet
Characteristics

P7T
APC Essential SurgeArrest, 7 outlet, phone line protection

Purchase

Purchase	P7T

Overview

Model Name	APC Essential SurgeArrest, 7 outlet, phone line protection
Includes	1.8 Meter Tel cable (2),User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Anguilla,Aruba,Bahamas,Barbados,Belize,Bermuda,Canada,Cayman Islands,Cuba,Dominican Republic,Guyana,Haiti,Puerto Rico,Trinidad And Tobago,Turks And Caicos Islands,United States,VIRGIN ISLANDS (UNITED STATES)

Output

Number of Outlets	7
Receptacle Style	NEMA 5-15R

Input

Nominal Input Voltage	120V
Input Frequency	50/60 Hz +/- 5 Hz (auto sensing)
Input Connections	NEMA 5-15P
Maximum Line Current per phase	15
Cord Length	1.83 meters

Surge Protection and Filtering

Surge energy rating	840
EMI/RFI Noise rejection (100 kHz to 10 mHz)	20
Peak Current Normal Mode	10
Peak Current Common Mode	30
Data Line Protection	RJ-11 Modem/Fax/DSL protection (two wire single line)
Let Through Voltage Rating	< 330

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Physical

Net Weight	0.64 kg
Maximum Height	318 mm
Maximum Width	76 mm
Maximum Depth	36 mm
Shipping Weight	0.77 kg
Shipping Height	353 mm
Shipping Width	133 mm
Shipping Depth	39 mm
Master Carton Units	12.0
Master Carton Dimensions (Length x Width x Height)	413 mm
SCC Codes	1073130420072 4
Color	Charcoal
Units per Pallet	504.0

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	CSA,UL 1363,UL 1449
Standard Warranty	Lifetime
Equipment protection policy	Lifetime : $25000
UL 1449 TVSS Rating	330V

Sustainable Offer Status

RoHS	Compliant